

#### Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

**Product Bulletin** 

Product Name: Aquapure Bio 20 Product Code: 2600003 Revision Date: May 22, 2020

# AquaPure™ Bio 20

Aquapure Bio 20 is a broad spectrum of bacterial cultures designed to degrade most industrial wastes. The cultures in Aquapure Bio 20 are capable of degrading phenols, alcohols, surfactants, detergents, glycols, naphthalene's, amines, nitriles, aliphatic and aromatic hydrocarbons, ketones, cutting oils, styrene, heterocycles, and low levels of cyanide. Aquapure Bio 20 will enhance BOD, COD and TSS removal in most all steel mill, pharmaceutical, chemical, and petrochemical wastewater treatment systems. The product can be used effectively for soil and groundwater remediation projects.

### **Features & Benefits**

| Broad spectrum culture   | Enhances BOD, COD and TSS |
|--------------------------|---------------------------|
| formulated to degrade    | removal                   |
| most industrial waters   |                           |
| A dry, free flowing      | May be added directly to  |
| powder                   | aeration tank, lagoon or  |
|                          | oxidation ditch           |
| Available in 1 lb. water | Ease of use, no operator  |
| soluble bags             | measuring                 |

### **Physical Data**

| Product:          | Dormant bacterial cultures and  |
|-------------------|---|
|                   | enzymes   |
| Form:             | A dry, free-flowing powder  |
| Color:            | Beige to light brown  |
| Specific Gravity: | 0.50 – 0.60   |
| Storage:          | Store product in a dry place between 10°C – 40°C. If product becomes wet, it must be used immediately. Do not freeze. |









#### Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

**Product Bulletin** 

Product Name: Aquapure Bio 20 Product Code: 2600003 Revision Date: May 22, 2020

### **Typical Applications**

- Steel mills
- Chemical Plants
- Petrochemical plant wastewater systems

## **Operating Conditions**

Product may be added directly to aeration tank, lagoon, or oxidation ditch. For trickling filters, it is best to perhydrate product by adding 2 lbs. per 1 gallon of 20°to 30° C non-chlorinated water. Allow solution to stand for 30 minutes to 2 hours before adding to trickling filter.

For soil and groundwater applications, consult your sales representative.

| рH          | 6.0 – 8.5     |
|-------------|---------------|
| Temperature | 10°C – 45°C   |
| PO 4        | 2mg/L minimum |
| NH3 N       | 2mg/L minimum |

Do not use in environments where high levels of toxic metals such as zinc, chrome, mercury, are known to exist.

#### Availability

Product is available in 25 lb. plastic pails or 100 lb. fiber drums

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

### Our people. Your problem solvers.

For more information on this process please call us at 1-800-648-3412

or techservice@hubbardhall.com











